



STAFF PROCEDURE

Don Turner, Chief Rangemaster *DT*

revised: 090100

STAFF PROCEDURE FOR: PAINT STANDARDS

The following paint type and colors will be used at BASF for all indicated uses. The supplier is Dunn-Edwards at 31st Ave and Bell Road.

TYPE OF PAINT: Permasheen (W901)

PERMASHEEN® (W 901)

100% ACRYLIC SEMI-GLOSS ENAMEL

A tough, durable, semi-gloss enamel designed to have excellent adhesion to many surfaces, including aged alkyd (oil based) enamels. Permasheen provides superior blocking resistance, making it an ideal choice for interior and exterior window frames, doors, and door jambs. Also ideal for previously painted trim and siding. Permasheen has excellent color retention, is nonyellowing, and cleans up easily with water.

Estimated coverage: 375 sq. ft. per gallon.
Dry to touch: 30 minutes Recoat: 2-4 hours

PAINT COLORS:

(PC2500)
Interior Walls
Ceilings
Baseboards

(PC2460) ←
Exterior Walls
Safety Walls
Safety Towers
Target Frame Holders
Garbage Cans

(PC2520)
Trim (Interior and Exterior)
Doors
Door facings
Wooden rails
Metal rails
Canopies and covers
Bathroom partitions

(SP 74 COCOA)
Fascia
Soffits
Gables
Rain gutters and down spouts
Stools
Wooden tables
Benches
Picnic tables
Brass buckets

PC 2500



PC 2520

PC 2460



SP 74 COCOA